

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 602 775 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention  
of the grant of the patent:  
**27.11.1996 Bulletin 1996/48**

(51) Int Cl.<sup>6</sup>: **G07F 7/04, G07D 7/00**

(21) Application number: **93307789.3**

(22) Date of filing: **30.09.1993**

(54) **Document handler with shutter**

Dokumenthandhabung versehen mit einer Klappe

Manipulateur de documents avec obturateur

(84) Designated Contracting States:  
**CH DE ES FR GB IT LI SE**

(30) Priority: **17.12.1992 EP 92121430**

(43) Date of publication of application:  
**22.06.1994 Bulletin 1994/25**

(73) Proprietor: **MARS INCORPORATED**  
**McLean, Virginia 22101-3883 (US)**

(72) Inventor: **Garcia Tinoco, Guillermo Jaime**  
**CH-1218 Geneva (CH)**

(74) Representative: **Musker, David Charles et al**  
**R.G.C. Jenkins & Co.**  
**26 Caxton Street**  
**London SW1H 0RJ (GB)**

(56) References cited:  
**WO-A-81/01211**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 0 602 775 B1**

## Description

### Field of the Invention

The present invention concerns the field of document handling apparatus, more particularly for banknotes.

Apparatuses of this type, for example banknote validators, referred to as selectors throughout the following, are integrated into automatic machines selling goods or a service to users. They are generally applied at the moment to suitable processing of banknotes and also of other documents of value such as certain standard types of cheques. Throughout the following, the term document will designate a rectangular sheet of paper or other material of suitable dimensions, introduced by the user into the selector, this sheet being recognised as a genuine note or not after authentication tests.

### Description of the Background Art

Known selectors may comprise an inlet aperture, widened out to a greater or lesser degree and protected from the weather to a greater or lesser degree, ending in a passage having a width greater than the width of the document and bounded by an upper face and a lower face. These two faces open into an inlet channel where the document is grasped by a transport means for the document, commonly termed a transport system, and consisting generally of a system of belts or rollers, cylinders, motor and pulleys. The setting in operation of the motor of this system is controlled by a control circuit or "processor", which acquires the necessary data in particular through a system for detecting the document in the aperture; this system comprises for example sensors which detect the presence of paper. The tests for authentication of the document themselves may take place in a second part of the selector, situated after the inlet channel. If the document is not recognised as a genuine note, it is directed towards a rejection outlet, which may be different from the inlet aperture or otherwise, in order to return it to the user, who is assumed to have acted in good faith.

If at the end of these tests the document is recognised as genuine, it is switched towards a box, intermediate or final, depending on the model of automatic machine. In the model with final box, any note recognised as genuine releases a transaction. In models with an intermediate box ("escrow"), the note is first stored in this intermediate box and its face value is credited. The transaction is released when the selling price is reached. If the user so wishes, he can cancel the request and his documents which have already been introduced are returned to him through the intermediate box. Such a device is described for example in the document FR-7909576.

It is known to obstruct the passage physically by means of a shutter, situated between the aperture and

the inlet channel. The obstruction of the inlet channel is intended to prevent any premature introduction of a further document into the aperture. The routines of acquisition and processing of the signals for detection of a document presented by the user lead to the setting in operation of the transport motor, then to the process of recognition of the document (cheque or banknote, currency of the note, face value) and to its authentication. These routines take what seems a long time to the user. If the latter then attempts to introduce a second document into the aperture and the inlet channel and the latter is not obstructed, the sensors for detecting the presence of paper then send signals to the processor which disturb the normal functioning of the processor.

The document FR-7909576 describes a shutter consisting of a smooth plate actuated by an electromagnet which opens it when a presence sensor detects the presentation of a document in the aperture. The document DE-2323839 describes on the one hand a shutter in the form of a rod sliding in a casing, the rod partially obstructing the passage of the document, and on the other hand a shutter having a width greater than that of the passage of the document, completely obstructing its passage.

In WO 81/01211 (and equivalent publications EP 0028089 and US 4348656), specifically in Figure 9 thereof, there is disclosed a banknote validator in which an inlet shutter comprises a cylinder carrying a slot therethrough to allow passage of a note in one orientation of the cylinder. However, there is no disclosure of the arrangement by which the shutter is rotated, or of the susceptibility of the shutter to vibration. Separately, in Figure 11a thereof, an arrangement showing a plurality of interengaging teeth is described.

The shutters of the known selectors have the drawback of being sensitive to vibration. If the automatic machine is fixed but subjected to tremors or vibrations, for example on an underground train platform on arrival of a train, or mounted on board a vehicle such as for example a train, these vibrations may open the shutter prematurely and thus permit the introduction of a second document. The second document may then interfere with the processing of the first document and lead to the rejection of genuine notes.

Linear mechanical vibrations fore and aft, up and down or from side to side of the apparatus can thus be converted by the pivotal motion of the inlet shutter (and, for that matter, other shutters or diverters in the apparatus) into substantial pivotal oscillations, depending on the resonances of the shutter.

### Summary of the Invention

The present invention solves this problem by providing that the mass of the assembly comprising the shutter and its actuating components (and other components which can move with the shutter) is distributed such that there is no turning movement or couple about

the axis around which the shutter pivots. In one embodiment, this is achieved by providing that the center of mass of the shutter and other components associated therewith lies on the axis about which it pivots. In another embodiment, other components which move with the shutter are pivoted about a further axis, and the mass of the system is so distributed that there is no couple about either axis.

The invention is employed particularly where the shutter, together with its associated actuating components, does not consist of a single rotationally symmetrical component of homogeneous mass mounted concentrically; for example, where it consists of a rotationally symmetrical shutter with an associated actuating arm extending away from the axis thereof, or where (as is the case, for example, in note diverter plates or outlet shutters) the shutter itself is not rotationally symmetrical. In a simple embodiment, the shutter may comprise an outlet shutter consisting of a plate-like flap pivoting around an axis, with a counterweight positioned on the other side of the axis thereto.

In another aspect, the present invention provides a pivotable shutter which is rotationally symmetrical about a pivoting axis, which carries projecting and/or recessed portions to engage with corresponding recessed and/or projecting portions in the surround to the shutter, to prevent a document passing between the surround and the shutter. This advantageously prevents jams in the region of the shutter, and attempts to defraud the apparatus.

In a particular form of embodiment of the invention, means are provided to modify the angular position of the shutter in response to the action of one or more systems for detecting the presence of paper. These detection systems are for example photodiodes, arranged upstream of the shutter in the aperture and/or downstream of the shutter, and connected to the processor, which generates a command to open the shutter when a document is presented in the aperture, then close the shutter when the signal sequence indicates that the document has passed the shutter.

In a particular form of embodiment of the invention, a shutter is approximately in the shape of a cylinder of revolution about a pivot axis and having a length greater than the width of the inlet aperture. A slot is provided in this cylinder to allow the document to pass through.

In relation to a device only partially obstructing the passage of the document, an advantage of the cylindrical shape is complete closure of the aperture. Some persons attempting fraud try to disturb the mechanism of the selector by introducing thin strips of paper into the aperture. With this cylindrical shape, the passage is completely closed and these attempts are unsuccessful.

In a particular form of this embodiment of the invention, the intersection between the surface of the cylinder and the two faces of the slot is rounded so as not to damage a document which might for example have been introduced immediately after a first document, be-

fore the order to close the shutter had been given by the processor.

A drawback of shutters offering a smooth surface to the leading edge of the document introduced into the aperture is that the document may stray into the space comprised between the shutter and its casing or its seating. In order to remedy this drawback, in another aspect of the invention, the intersection between the surface of the cylinder and the plane of movement of the document is non-rectilinear, consisting for example of a broken line. The same form of line is adopted for the two faces of the aperture and of the inlet channel, this line being able for example to be in the shape of grooves provided in the surface of the cylinder and in which there circulate teeth provided at the end of the two faces of the aperture and of the inlet channel. These teeth prevent the document from straying between the shutter and its surround.

When the shutter is brought into the "open" position by the detection of a document in the aperture, a detector for detecting the presence of paper, situated downstream of the shutter, is first of all typically occluded by the leading edge of the document which is passing through the slot of the shutter, then de-occluded by the trailing edge of the document, once the shutter is passed. The processor then causes a rotational movement of the device through an angle sufficient to ensure closure by the shutter.

In a particular form of embodiment of the invention, the drive means of the shutter consist of an electromagnet (e.g. a solenoid), the rest position of which corresponds to the closed position, and the actuated position to a maximum opening position of the shutter. In this form, which has the advantage of simplicity and moderate cost, the pivoting angle permitted for the shutter may be not in excess of 30 to 45°. It is possible in this form to reduce the total dimensions of the selector by judicious placing of the electromagnet.

In one arrangement of this particular form of embodiment of the invention, it is possible to prevent vibrations, generally random in direction, from disturbing the proper functioning of the drive means, by providing on the one hand a mechanical means for the return of the shutter to its closed position, this means bearing on a fixed stop, and on the other hand unilateral driving of an arm, rigidly connected to the shutter, by the plunger of the electromagnet. In this way, if the plunger is affected by the vibrations, it does not take with it the arm rigidly connected to the shutter when the latter is at rest. When the electromagnet is actuated, the vibrations of the plunger may temporarily disturb the introduction of the document into the slot of the shutter. This is less troublesome, and can be corrected by providing the slot with the asymmetric shape of a venturi. In this way, the slot has a supplementary function of guiding the leading edge of the document which persists even in the case of vibration in the open position.

Embodiments of the invention may make it possible

to nullify attempts at "string" fraud. In this type of fraud, the person attempting fraud attaches to a document threads, strings, tapes or other means of acting on the position of the document from the outside, when the transport system alone is supposed to transport the document. In certain cases, the person attempting fraud attaches together two documents, only one of which, for example, is a genuine note. When the automatic machine comprises a rejection outlet different from the aperture, he may thus hope that the false document, once it has been refused, will bring the genuine document along behind it.

In a form of embodiment of the invention where the shutter turns through an angle of less than 180°, and where the slot is always presented in the same direction to the aperture, there can be incorporated in the slot a device detecting the presence of "strings" attached to the document. This device, particularly suitable for the detection of wide or relatively rigid "strings", may for example consist of a secondary shutter obstructing the slot in the closed position where the direction of the slot is close to the vertical. This secondary shutter can come automatically into position simply by gravity and, by nipping the strings, exerts a braking action on the document at the moment when the transport system grasps and conveys the document.

In a particular form of embodiment of the invention, the slot of the shutter is symmetrical in relation to the axis of the cylinder, and the position of the shutter does not depend on any stop or any passive return means. In this case, rotations of the shutter through any angle whatever, but still equal to an odd number of times 90°, mean that the shutter passes alternately from the open position, in which the slot is parallel to the direction in which the document is introduced, to the closed position, in which the slot is perpendicular to that direction.

In a particular form of embodiment of the invention, provision is made for rotation to take place normally always in the same direction.

In another form of embodiment of the invention, the direction of rotation can be controlled by the processor, which is moreover capable of checking precisely the position of the shutter. This checking may be effected by means of a position detector on the one hand, consisting for example of an encoder disc rigidly connected to the shutter and coupled to a plurality of assemblies of fixed optical emitters and receivers, and on the other hand by a precise control of the motor driving the shutter, which may for example be a stepping motor or a motor with reduction gear. In this form of embodiment of the invention, the processor can be programmed so that it causes the shutter to rotate by a determinate multiple of 90°, the value of which multiple takes into account whether the slot is or is not symmetrical in relation to the axis of the cylinder. The encoder disc may for example comprise a defined number of slots on its periphery, the distance between these slots and the axis of rotation common to the disc and to the shutter being selected so that

the beams of the optical emitter and receiver assemblies are occluded or de-occluded in succession, according to a sequence recognisable by the processor.

It can be imagined that if the processor is programmed so that it causes the shutter to turn through a certain multiple of 90°, for example during the course of a checking routine after the passage of a document into the slot, any strings will be trapped between the shutter and its seating.

In a particular form of embodiment of the invention, in order to prevent the user from inserting a new document into the slot during such a routine where the shutter passes several times through an open position, it is possible to provide two successive shutters, the first, for example of a conventional type, obstructing the passage and the second, of a rotary type, serving to detect any strings.

In an aspect of the invention, means are provided in addition to permit the processor to detect quickly, before total paralysis of the selector or overheating of the drive means of the shutter, if the document is slowed down or stopped by strings which are nipped between the shutter and its seating. For this purpose, a mechanical return means, such as for example a spring, may be provided between the shutter and its drive means, coupled to a contact which closes in the case of tension of this spring. The signal sent to the processor by the closure of this contact leads to the conclusion that there is an attempt at fraud and to a decision to return the document even before having started the authentication tests. Another possible means of detecting an incorrect velocity of the document is the instantaneous calculation of its velocity by means of the information provided by the systems for detecting the presence of paper, for example CCD diodes, and its comparison with the nominal value corresponding to the speed of the motor driving the belts. This aspect can be used independently of the features of the main claim.

In a particular form of this aspect of the invention, control by means of a bistable electromagnet eliminates the risk of heating up.

It may be advantageous, in the case where the maintenance personnel is not alerted after the automatic machine has been put out of service, to thwart the attempts at fraud enough to discourage the person attempting fraud, without however putting the apparatus out of service. For this purpose, in a particular form of embodiment of the invention, provision is made, when the processor has detected an attempt at fraud, for the person attempting fraud to be deceived by simulating a breakdown caused by this attempt at fraud, this simulation of a breakdown taking place only during a limited time lag, but sufficient for the person attempting fraud to be discouraged. In this aspect of the invention, the processor, during the whole of the time lag, causes the shutter to turn in the opposite direction to normal, until the shutter is brought into the initial position which it occupied at the moment of introduction of the document

having generated the fraud signal. This manoeuvre, or other programmable disengagement routines, eliminates the traps in which the strings are jammed. Once the causes of the braking of the document have been eliminated, the document is then directed towards an auxiliary box, different from the intermediate or final box, wherein doubtful notes are stored for subsequent manual sorting. In such a case, the operating time of the motor of the transport system can be extended to finish freeing the passage, even when the strings are very long. Even if in such a case the person attempting fraud succeeds in withdrawing his document by means of the strings remaining accessible from the outside, the processor can keep in its memory the data of the incident, in order to make it possible to recognise more fully and analyze the types of fraud. This aspect of the invention is useful independently of the features of claim 1.

The above routine can be improved by increasing the time lag if several attempts at fraud are detected following one after the other. In this way, it is possible gradually to discourage even persons attempting fraud who after a first attempt, made, for example, at a time of day when the automatic machine is little used, would then be diverted towards other automatic machines of the same station.

In a particular form of embodiment of the invention, the user is asked to wait before introducing the following document by an optical signal such as for example a red indicator light and a green indicator light, the red indicator light going on when the processor orders the closure of the shutter and the green indicator light going on once the selector is available for handling a new note.

The invention may advantageously be used in a banknote validator as described in our earlier International Application PCT/CH93/00095, published as WO 93/21609 (agents Ref: J.25168 WO).

Furthermore, the features of our earlier UK application GB9314404.6 published as GB-A-2280057 (agents Ref: J.25183 GB) are also useable with the present invention.

#### Brief Description of the Drawings

Other advantages of the invention will be revealed by the detailed description which follows, with reference to the accompanying drawings in which:

Figure 1 shows a sectional side view of the selector and of the shutter according to a first form of embodiment;

Figures 2 to 4 show a side view of a vertical section through the aperture of the selector and the shutter according to the same form of embodiment;

Figure 5 shows, on the same scale, a side view of an encoder disc rigidly connected to the shutter, the latter being in the closed position;

Figure 6 shows a partial view of a particular form of embodiment of the encoder disc in Figure 5;

Figure 7 shows a top view of the shutter in the position in Figure 2 with a first form of embodiment of the grooves;

Figure 8 shows a partial top view of a second form of embodiment of the invention, corresponding to the position in Figure 10, and wherein the shutter has a second form of embodiment of the grooves;

Figure 9 shows a profile view of the second embodiment of the invention, the relay being at rest;

Figure 10 shows the same profile view of the second embodiment of the invention, the relay being under tension;

Figure 11 shows a side view of a third embodiment of the invention; and

Figure 12 shows a corresponding front view; and Figure 13 shows a sectional side view corresponding to that of Figure 11 and illustrating the far end of the same embodiment;

Figure 14 is a plan view illustrating the engagement of the shutter of the same embodiment with its surround;

Figure 15 shows a sectional side view of an outlet shutter according to a fourth embodiment of the invention;

Figure 16 corresponds generally to Figure 1 and illustrates a diverter according to a fifth embodiment of the invention; and

Figure 17 is a detail of Figure 16 and shows the diverter according to the fifth embodiment of the invention in greater detail;

Figures 18 to 20 show other embodiment of the invention.

#### First Embodiment

Figures 1 to 7 show the functioning of a cylindrical shutter 5 according to a first form of embodiment.

Figure 1 shows a side view of a vertical section through the aperture 16 of the selector, the inlet channel 26, the shutter 5, the motor 19, the inner part 22 of the selector located downstream of the shutter, and also diagrammatic representations of the processor 21, the transport path 23 including occupation detectors 27, a stacking piston 24, and also an outlet shutter 25.

The cylindrical shutter 5 is equipped with a slot 11 placed longitudinally, permitting the passage of documents. It is movable in rotation about an axis 18 (Figure 7).

The arrow 1 designates the direction in which the documents 20 are introduced, and the arrow 2 the normal direction of rotation of the cylindrical shutter 5 about the axis 18.

The drive unit 19 is in this case a stepping motor or a motor with reduction gear. An encoder disc 10 with several windows 12 is rigidly connected to the cylindrical shutter 5, the centre of gravity of the assembly being located on the axis 18, which makes the angular position of the cylindrical shutter 5 insensitive to vibration. The

encoder disc 10 functions with two assemblies emitting and receiving optical beams 14, 15, located opposite the windows 12 for checking the position of the cylindrical shutter 5, the whole being associated with detectors 3, 4 located in the input channel 26 and on the inside 22 of the apparatus to detect whether the documents 20 have passed the slot 11 and are completely in the inner part 22 of the selector, downstream of the shutter 5.

The input channel 26 comprises two faces 6, 7 provided in the manner of a comb, the teeth of which enter grooves 17 of the cylindrical shutter 5, preventing the document 20 from passing round the cylindrical shutter 5 on introduction into the slot 11 or on leaving the slot 11 towards the inner part 22 of the selector located downstream of the shutter.

The processor 21 orders the rotation of the shutter 5 by way of the motor 19 if neither of the two detectors 3 and 4 detects the presence of a document. If the detector 3 detects the presence of a document, the motor 19 rotates the shutter 5 into the position shown in Figure 2 or 4. If the detector 4 detects the presence of a document, the shutter is maintained in the position in Figures 2 and 4.

The transport path 23 conveys the document 20 through an authentication sub-assembly of the selector, for example such as described in US Patent 3 227 256, then stores it in a position where it can be enclosed in an intermediate or final box, according to a device as described for example in Patent Application FR-2 453 811, by means of a stacking piston 24. If the document 20 is not recognised as genuine following the authentication tests, the processor 21 orders the opening of the outlet shutter 25 and the transport system conveys the document 20 as far as the outlet shutter 25, where it is recovered by the user.

The occupation detectors 27 of the transport path 23 serve to detect the presence of a document 20 in the inner part 22 of the selector located downstream of the shutter 5. They may consist for example of CCD diodes, and supply the processor with information concerning the state of occupation of the transport path 23. This path only becomes free when a document 20, once the detector 4 is de-occluded, has either passed the outlet shutter 25 or been boxed by the stacking piston 24, as described hereinafter.

Figures 2 to 4 show the functioning of the shutter in a particular example where the cylindrical shutter 5 rotates from the position shown in Figure 1 always in the same direction of rotation 2, with four defined stop positions at 90°, 180° and 270° with respect to the plane of introduction of the documents 20 into the aperture 16. The position at 360° corresponds to a return to the position in Figure 1. These positions are detected for example by two optical beams 14, 15 in the following manner:

- when only the outer beam 14 is de-occluded by a single window 12, the shutter 5 is in the open position,

as indicated in Figures 2 and 4;

- when the two beams 14 and 15 are de-occluded by the windows 12, the shutter 5 is in the closed position described with reference to Figures 1 and 3;
- when neither of the two beams 14 and 15 is de-occluded by any window 12, the shutter 5 is in an intermediate position between the open position and the closed position.

The cylindrical shutter 5 in Figure 1 prevents access to a document 20 at the inner part 22 of the selector.

#### Processor 21

The processor 21 receives information both from the detectors 3 and 4 and from the optical beams 14 and 15 and the occupation detectors 27. It utilises all the information simultaneously according to a scheme described hereinafter to act on the control of the stepping motor 19 in such a way that the information received from the optical beams 14 and 15 corresponds to the nominal value as determined in a certain number of different states of the selector:

- a state 100 corresponds to a de-occluded diode 3, a de-occluded diode 4, the transport path 23 free. In this state 100, the shutter 5 should be closed and the instruction is that the two optical beams 14 and 15 should be de-occluded.
- a state 10A corresponds to a de-occluded diode 3, a de-occluded diode 4, at least one of the occupation detectors 27 occluded, which means that the transport path 23 is occupied. In this state 10A, the shutter 5 should be closed and the instruction is that the two optical beams 14 and 15 should be de-occluded.
- a state 200 corresponds to an occluded diode 3, a de-occluded diode 4, the transport path 23 free. In this state 200, the shutter 5 should be open, and the instruction is that only the optical beam 14 should be de-occluded.
- a state 300 corresponds to an occluded diode 3, an occluded diode 4, the transport path 23 free. In this state 300, the shutter 5 should be open, and the instruction is that only the optical beam 14 should be de-occluded.
- a state 400 corresponds to a de-occluded diode 3, an occluded diode 4, the transport path 23 free. In this state 400, the shutter 5 should be open, and the instruction is that only the optical beam 14 should be de-occluded.
- a state 500 corresponds to a de-occluded diode 3, an occluded diode 4, the transport path 23 occupied. In this state 500, the document 20 is already engaged on the transport path but has not yet passed the detector 4. This state can detect an anomaly such as an attempt at "string" fraud. It may then be decided that the shutter 5 should for exam-

ple be open, so as not to hinder the progress of the note, and the instruction is then that the two optical bundles 14 and 15 should be de-occluded. In such a case, the transport path can be actuated and the outlet shutter 25 opened until the document 20 is discharged, after which the system is back in the state 100 and the shutter 5 is closed.

a state 600 corresponds to a de-occluded diode 3, a de-occluded diode 4, the transport path 23 occupied. In this state 600, the shutter 5 should be closed and the instruction is that the two optical beams 14 and 15 should be de-occluded.

As will be seen, other information reaching the processor 21 can lead to the same routines of discharge of the document 20 as those corresponding to the state 500.

As soon as the document 20 is completely in the inner part 22 of the selector downstream of the shutter 5, two cases are possible: the first in which there is a document 20 only, and the second case in which the document 20 has been introduced by a person attempting fraud who has placed strings 13 (indicated by dotted lines in Figures 2 to 4) at the rear of the document 20.

In both cases, when the detectors 3 and 4 are de-occluded after the passage of the first document 20, the motor 19 again causes the shutter 5 to rotate through 90° (Figure 3) into a stop position of 180°, which makes it possible :

a) In the first case to prevent the introduction of a second document 20 while the first is being processed. Once the processing of the first document 20 is terminated and the apparatus detects the presence of a second document 20 at the aperture 16, the cylinder rotates again through 90° (Figure 4), thus permitting the entry of the second document 20; as soon as the latter is completely inside the apparatus, the cylinder rotates through 90° to be once more in the position described with reference to Figure 1 and to recommence the sequence.

b) In the second case to start to wind the strings 13 round itself. Once the processing of the first document 20 is terminated and the apparatus detects the presence of a second document 20 in the aperture 16, the cylinder rotates again through 90° (Figure 4).

In the case where the shutter 5 can rotate in both directions, the position checking system with the encoder disc 10 makes it possible to detect forward or reverse movement starting from the closed position of the shutter 5, brought about by strings or any kind of instrument, and at the same time to check whether it has not been blocked, forced or turned to perpetrate a fraud or to damage it.

### Position Identification

Figure 5 shows a first example of a device making it possible to identify the open or closed position of the cylindrical shutter 5, and to send a corresponding signal to the processor 21. In this device, the slot 11 is symmetrical, which means that rotation of the cylindrical shutter 5 through 180° brings it into the position for receiving a new document 20. This device comprises an encoder disc 10 rigidly connected to the shutter 5, itself comprising four points of reference consisting, according to the case, of one or two windows 12 of small dimensions.

It furthermore comprises, as will be seen in Figure 7, two assemblies 14, 15, each consisting of an optical emitter and receiver, known *per se*, inserted into the seating of the cylindrical shutter 5 in such a way that the encoder disc 10 masks or allows through a beam of light passing from the emitter to the receiver of each of the two assemblies 14, 15. In the example shown in Figures 1 to 5, the position of the encoder disc 10 corresponding to the closed position of the cylindrical shutter 5 is that in which two windows 12 allow the two beams to pass. The position of the encoder disc 10 corresponding to the open position of the shutter, as can also be seen in Figures 2 and 4, is that in which only the window furthest from the axis of rotation allows the beam 14 to pass.

This device allows the processor 21 to be certain of the position of the cylindrical shutter 5 and, by counting the pulses received in sequence by each receiver, of the total angle of rotation of the cylindrical shutter 5. If the slot of the latter is not symmetrical but is arranged to admit the documents in only one direction, it is sufficient to omit the corresponding window in the encoder disc 10. This device also allows the processor 21, by comparison of the information thus received with that coming from the drive means 19 of the cylindrical shutter 5, for example a stepping motor or a motor with reduction gear, to detect abnormal braking of the rotation of the cylindrical shutter 5 by slipping of a clutch, or by tensioning of a spring or other deformable mechanical device serving as a means of transmission between the stepping motor 19 and the cylindrical shutter 5. This abnormal braking may allow it to be reliably concluded that there are strings 13 winding themselves round the cylindrical shutter 5.

Likewise, when the document 20 is driven by the transport system and for example one of the strings 13 is nipped in a groove 17 of the cylindrical shutter 5, it drives the latter in rotation, thus modifying the positioning signal sent by the receivers of the beams 14, 15. There also the processor 21 can immediately conclude that a fraud is being perpetrated and can treat the document 20 accordingly, that is to say, by discharging it through the transport path 23 as far as the previously opened outlet shutter 25. This treatment may for example utilise the same routine as for example that initiated by the state 500 described previously.

Figure 6 shows another example of the device for identifying the position of the shutter. In this form of embodiment, the encoder disc 10 comprises several windows 12 distributed over its periphery. The angular position of the shutter can be identified for example by providing each window 12 with optical properties recognisable by the receivers of the beams 14 and 15, for example a shape or dimensions particular to each window, or by installing in each window an element which is translucent but of a specific colour. The colour recognition device can then advantageously utilise elements used within the framework of the authentication process for the notes.

### Second Embodiment

Figures 8 to 10 show a second, simpler form of embodiment of the invention, wherein the grooves 17 have a notched shape, and correspond to teeth (not shown in Figures 8 to 10) of corresponding shape at the end of the faces 6, 7 of the aperture and of the corresponding faces of the inlet channel 26.

An arm 8 rigidly connected to the shutter controls its rotation between two angular positions shown in Figures 9 and 10. The arm 8 is driven by the plunger 9, terminated by a small roller, of an electromagnet 19.

In Figure 9, the control circuit of the electromagnet 19 is open. No part of this electromagnet 19 is in contact with the arm 8 or with the cylindrical shutter 5, which is maintained in the closed position in Figure 9 by a return spring, not shown, bearing on a stop linked to the frame and bringing the arm 8 back in the opposite direction to the direction of rotation 2 in Figure 1. As the centre of gravity of the assembly 5, 8 is located on the axis 18 in Figure 8, the slot 11 is not sensitive to vibrations capable of affecting the frame in this position.

In Figure 9, the control circuit of the electromagnet 19 is closed. The plunger 9 pushes back the arm 8, bringing the cylindrical shutter 5 into the open position. The slot 11 is widened out into a flared portion ("venturi") so that any vibrations affecting the plunger 9 do not compromise the stability of the open position in Figure 10.

Instead of an electromagnet, an electric motor can be provided as drive means for the shutter 5 in Figures 9 and 10.

### Third Embodiment

Referring to Figures 11-14, a further embodiment of the invention will now be illustrated.

Referring to Figure 11, in this embodiment, the inlet channel 26 may be as disclosed in the earlier embodiments. The shutter 5 comprises a slot 11 defined between upper and lower portions of a cylinder 28.

Referring to Figure 12, the cylinder 28 is mounted on stub axles 29a, 29b each in a rotary bearing (e.g. a ball race) in a respective sidewall 30a, 30b of a banknote validator. An arm 8a projects outwardly and downwardly

from the cylinder 28 and is mounted fixedly thereto, so that swinging the arm 8a causes the cylinder 28 to rotate about the axis running through the axles 29a, 29b. The outermost portion of the arm 8a carries a fork 31, which receives a pin 32 carried upon the upper end of a lever arm 8b. The lever arm 8b pivots about a lower axle 33, which is likewise carried between the two sides 30a, 30b of the validator. The lever arm 8b is conveniently attached to the axle 33 by an expandable arcuate clip 34 of a plastics material. On the other side of the axle 33, the lever arm 8b extends and carries a counterweight arrangement 35, conveniently comprising a pair of metal weights 35a, 35b retained in corresponding arcuate expandable clips 36a, 36b of a plastics material.

Located within the lever arm 8b is a slot 37 within which a pin 38 is trapped, the long walls of the slot 37 being generally inclined parallel with the axis of the lever arm 8b. The pin 38 is fixed to the actuator (i.e. the core) 9 of a solenoid 39, solid with the wall 30a of the validator.

Thus, actuating the solenoid 39 in this embodiment causes linear movement of the core 9, which is translated into a pivoting of the lever arm 8b around the axis of the axle 33 by the slot 37. This in turn causes rotation of the arm 8a by the action of the pin 32 on the slot 31 therein, and in turn rotates the cylinder 20a and slot 11 into or out of alignment with the entrance channel 26.

As the total actuating length of the solenoid plunger 9 is generally only of the order of 4-5 mm of travel, conventionally it has been hard to use a solenoid or similar linear actuator device to actuate a rotary shutter. In this embodiment, it is desired to rotate the shutter through 45° between the open and closed states, and this would conventionally be difficult to achieve.

However, in this embodiment, it will be seen that the length of the lever arm 8b provides some multiplication of the rotation applied by the solenoid plunger 9; as the pin 32 is located further away (in this embodiment, over twice as far) from the axle 33 than the slot 37, the length of the arc through which the pin 32 is rotated by motion of the plunger 9 is larger by a corresponding factor. On the other hand, the length of the arm 8a is very much shorter, and so the travel of the pin 32 is converted by the slot 31 into a very much larger angular rotation of the arm 8a. To a first approximation, the amount by which the arm 8a (and hence the slot 11) rotates is in the same ratio to the angle through which the lever arm 8b rotates as the ratio between the relative lengths of the arms 8a and 8b.

Thus, by utilising a lever arrangement to multiply the rotation caused by an actuator (e.g. the solenoid 39), an actuator with a small total travel such as a solenoid can be employed to generate a large rotation of the shutter 5.

Referring to Figure 13 and Figure 12, the cylinder 28 also carries, at the opposite end thereof to the arm 8a, a downwardly projecting arm 40 carrying an arcuate interruption surface 41 in the form of a cylindrical arc concentric with the cylinder 28. The surface 41 is positioned so as to be swingable into a slot 42 defined by



upper and lower surfaces 43, 44. In one of the surfaces is located a light source 45a (e.g. a LED) and in the other is located a light detector 45b (e.g. a photodiode). When, as shown in Figure 13, the shutter mechanism is closed and the slot 11 is misaligned with the inlet channel 26, the interruption surface is not within the slot 42 and the light beam between the light source 45a and the detector 45b is uninterrupted. When the shutter mechanism is pivoted in the direction 2, on the other hand, the interruption surface 41 enters the slot 42 and interrupts the light path between the light source 45a and the light detector 45b, allowing motion of the shutter 5 between the open and closed position to be monitored by the control circuit 21 connected to the light detector 45b.

With the arrangement of Figures 11-13, the relatively long lever arm 8b would normally be highly susceptible to vibration, which would then be transmitted to the arm 8a to cause the shutter 5 to vibrate which is in itself undesirable. Furthermore, the arm 40 is also highly susceptible to vibration, both transmitted from the cylinder 28 due to vibration of the lever arm 8b and directly induced in the arm 40. Vibration in the arm 40 is undesirable because it can cause the interrupting surface 41 to oscillate, causing rapid alternations between the interrupted and uninterrupted state of the light beam and giving rise to confusion as to the position of the shutter 5, and possible malfunction of the control circuit 21 as a result.

Accordingly, in this embodiment, the function of the counterweight arrangement 35 is to provide a counterbalance for the lever arm 8b, on the other side of the axle 33. However, the weight of the arm 8a, the plunger 9, and the arm 40 (and any other components which are moveable with the lever arm 8b, and are not already effectively counterbalanced by virtue of the mounting around the axles 29a and 29b) can simultaneously be stabilised by the counterweight arrangement 35. Thus, the counterweights 35a, 35b are selected so as to counterbalance not only the lever arm 8b but also the lever arm 8a, the plunger 9 and the swinging arm 40 an interrupting surface 41. It will be evident therefore, that longitudinal movements of the validator apparatus (i.e. movements generally transverse to the line between the two axles 29a and 33) are not translated into arcuate oscillations of the shutter 5 because of the counterweight arrangement 35.

The weight and position of the counterweight arrangement 35 is found by finding the centres of gravity of the arm 8a, the arm 8b, the solenoid core 9, and the swinging arm 41; finding the center of gravity of these centres of gravity; and arranging the counterweight mechanism to occupy a corresponding position and having a corresponding mass on the opposite side of the axle 33.

With this arrangement, there is not net movement about either the axis 29 or the axis 33 for any part of the shutter and actuating assembly. Thus, when a linear force is applied to the either of the axles 29 or 33 by a

mechanical vibration of the entire device, no couple is created and hence no torque exists to twist any part of the assembly around an axle; the tendency of the arms 8a, 8b, and 9 to move to and fro between the axles 29, 33 is opposed by the counterweight 35 and vice versa.

Thus, this arrangement achieves exactly the same effect as the arrangement of Figures 9 and 10, in which the center of gravity of the shutter 5 and arm 8 is positioned on the rotational axis of the shutter 5, so that there is no net couple about that axis.

It would, of course, be possible to provide additional or alternative counterweighting arrangements solid with the arm 8a but on the opposite side of the axles 29a, 29b, so as to position the centre of gravity of some or all of the arrangement on the axle 29a, 29b, as in the above embodiments. However, the present embodiment achieves a relatively compact construction.

Referring to Figure 14, as in the embodiments of Figures 7 and 8, the diverter is provided with a number of recess 17 along its length, interrupted by teeth 60 comprising, in this embodiment, eccentric arcuate segments (although this is not essential). The interengagement of the recesses 17 and teeth 60 with corresponding castellations in the surround portion 70 between the mouthpiece 16 and the shutter 5 prevents banknotes from being slid around the shutter 5 rather than through the slot 11, and thus helps to prevent jams or fraud.

#### Fourth Embodiment

In this embodiment, the outlet shutter 25 is also counterweighted to prevent vibration. In this case, the arrangement is less complex; as shown schematically in Figure 14, the outlet flap 25 pivots on an axle 46, on the opposite side of which is positioned a counterweight 47. The flap 25 is arranged to be urged to a closed position by a weak spring arm 48 and to be opened by the pressure of the leading edge of a banknote. Thus, because in this embodiment the outlet shutter 25 is counterbalanced, it is immune to vibrations as discussed above.

As illustrated in Figure 15, in this embodiment the counterweight is positioned on the opposite side of the axle 46 on which the shutter 25 pivots so that the centre of gravity of the shutter and counterweight combination lies on the axle 46 (or close thereto). However, a more complex counterweighting arrangement as shown in the embodiment of Figures 11 to 13 could equally be employed.

This embodiment is advantageously combined with any of the foregoing embodiments, so that both the inlet flap and the outlet flap are counterbalanced. The arrangement is particularly suitable to be provided in a selector apparatus which can be used in either vertical orientation, since the positions of the effective centres of gravity of the inlet flap assembly and the outlet flap assembly are unchanged by turning the apparatus upside down. There are many applications where this may be

desirable, for example, for reasons of space.

#### Fifth Embodiment

In the first described embodiment, a stacking piston 24 is provided to selectively load an accepted banknote into a cashbox.

However, referring to Figure 16, in this embodiment the stacking piston 24 is replaced by a diverter mechanism 49. The diverter mechanism is moveable between two positions; in a first ("closed") position it does not obstruct the path of a note towards the outlet shutter 25, whereas in a second ("open") position it blocks the passage to the outlet shutter 25 and instead diverts a note outwardly of the apparatus towards a cashbox or escrow.

Referring to Figure 17, in this embodiment the diverter 49 comprises a generally plate shaped member extending across the width of the note path 23 and pivotable about an axle 50. The diverter 49 is pivoted by an actuator (not shown, but conveniently comprising a further solenoid acting against a biasing spring).

Positioned on the diverter 49 (shown on the other side of the axle 50 from the note engaging end of the diverter 49) is a counterweight 51 of a sufficient weight to position the centre of gravity of the diverter, including the counterweight 50 and the actuator, on the axis running through the axle 50.

When the diverter 49 is in the position shown, it blocks the passage of a note towards the outlet shutter 25, whereas when it is rotated in the direction 2, it presents a diverting surface permitting the note to pass on towards the outlet shutter 25. The diverter 49 is actuated by the control circuit 21 in response to a valid/invalid decision thereof, to either pass the note outwardly of the path 23 and to a note store or to reject the note through the outlet shutter 25.

In this embodiment, as in the above embodiments, improved resistance to vibration is provided and thus the chance that a note passing towards the outlet shutter 25 will become jammed as it passes the diverter 49 is reduced.

Conveniently, this embodiment is employed together with any of the foregoing embodiments.

Particularly preferably, the diverter 49 in this embodiment may be as described in our British patent application No. 93 (agents Ref: J. 25186 GB) filed on the same day as the present application and incorporated herein by reference.

#### Further embodiments

Figures 18, 19 and 20 show further exemplary embodiments of the shutter according to the invention, accompanied in each case by the diagrammatic representation of an encoder disc.

Figure 18 shows an exemplary embodiment of the invention in which the shutter, made of a homogenous

material of uniform volume mass, comprises two slots at 90° to each other. In this exemplary embodiment, rotation through an angle of 45° is sufficient to pass from the open position of the shutter to the closed position, and vice versa.

Figure 19 shows an exemplary embodiment of the invention in which the shutter, likewise made of a homogeneous material of uniform volume mass, still comprises two slots, but parallel to each other. Also shown are the inlet channel and the inner part of the selector downstream of the shutter, to show that the axis of rotation of the shutter is not in this example situated in the plane of introduction of the document. In this exemplary embodiment, rotation through an angle of 90° is necessary to pass from the open position of the shutter to the closed position, and vice versa. Each slot is still traversed in the same direction by an incoming document, which makes it possible in this example to provide a venturi, or a guide means, or a non-return device, without thereby necessitating rotation through 360° between two open positions of the shutter.

Figure 20 shows an exemplary embodiment of the invention in which the shutter has an asymmetrical shape in relation to its axis of rotation. This is possible, for example, by constructing the shutter in two parts produced from two different materials, on either side of the slot, the volume masses of the two materials being such that the centre of gravity of the assembly is nevertheless located on the axis of rotation. This exemplary embodiment shows that there is no limitation with regard to the external shapes of the shutter, which can meet other requirements without departing from the scope of the invention.

#### **Claims**

1. A shutter arrangement for a document handling apparatus comprising a channel (26), a shutter (5) capable of obstructing the channel (26, 11, 22) and pivotable about a pivot axis (18) into or out of the plane of the document (20); the shutter having other components (8) arranged to move therewith (e.g. for actuating the shutter) so as to define a moving assembly, characterised in that the mass of said moving assembly (5,8) is so distributed that the assembly does not exhibit any turning moment about said pivot axis (18) on vibration of the document handling apparatus to which the pivot axis (18) is connected.
2. A shutter arrangement according to Claim 1 in which the center of gravity of the arrangement is located on the pivot axis (18).
3. A shutter arrangement according to Claim 1 which comprises an elongate actuating member (8) extending away from said pivot axis (18), said shutter

- (5) being connected to said member (8) so that actuation of said member (8) pivots said shutter (5).
4. A shutter arrangement according to Claim 1 or claim 3 further comprising a second pivot axis (33), and actuating means (8b,9) for actuating said shutter (5), said actuating means (8b,9) pivoting about said second pivot axis (33), further comprising a counterweight arrangement (35) acting around said second axis to balance the mass of the assembly so that it exhibits no turning moment.
  5. A shutter arrangement according to any preceding claim, in which said channel (26) is an inlet channel to said document handling apparatus.
  6. A shutter arrangement according to any one of claims 1 to 4 in which said channel (26) is an outlet channel leading to a document outlet of the document handling apparatus.
  7. A shutter arrangement according to any one claims 1 to 4 in which the channel (26) branches into a plurality of outlet branches, and the shutter comprises a diverter (49) for selecting one of said outlet branches.
  8. A shutter arrangement according to any preceding claim, comprising shutter drive means (19) actuated by a control circuit (21) acting in response to the action of one or more systems (3, 4) for detecting the presence of paper in order to close the shutter (5) by actuation of the drive means (19).
  9. A shutter arrangement according to any preceding claim, in which the shutter (5) obstructs the channel (26,11,22) over the whole of its width.
  10. A shutter arrangement according to any preceding claim, in which the channel (26) is equipped with features engageable with cooperating features (17,60) provided in the shutter (5) to prevent the document (20) from passing round the shutter (5).
  11. A shutter arrangement according to any preceding claim, in which the shutter (5) has a shape resembling that of a cylinder of revolution about the axis (18), and that at least one slot (11) is provided through the shutter (5) to permit the passage of the document (20) in at least one defined angular position of the device.
  12. A shutter arrangement according to Claim 11, in which the slot or slots (11) are symmetrical in relation to the axis (18).
  13. A shutter arrangement according to Claim 11 or claim 12, in which there is only one slot (11).
  14. A shutter arrangement according to any of claims 11 to 13, in which that the or each slot (11) comprises a flared inlet portion allowing the document (20) to be guided into the said slot (11).
  15. A shutter arrangement according to claim 11, in which the shutter (5) comprises two slots approximately normal to each other.
  16. A shutter arrangement according to Claim 11, in which the shutter (5) comprises two slots, preferably generally parallel to each other, the pivot axis (18) being outside the plane of introduction of the document (20) into the aperture (16).
  17. A shutter arrangement according to claim 11, in which the shutter (5) is produced in several parts consisting of materials of different density distributed at different distances from the pivot axis (18).
  18. A shutter arrangement according to any preceding claim, further comprising means (10, 12, 14, 15) for identifying the position of the shutter (5).
  19. A shutter arrangement according to claim 18 in which the identification means comprise an encoder disc (10) connected to the shutter (5) to move therewith.
  20. A shutter arrangement according to claim 19 in which the positions of the shutter (5) identified by the encoder disc (10) are at least four in number and uniformly spaced, two of the said positions corresponding to the complete opening of the shutter (5) and two others to its complete closure, and in which the processor (21), in response to the action of the identification means (10, 12, 14, 15), may order the rotation of the shutter (5).
  21. A shutter arrangement according to any preceding claim, comprising means for detecting stress on the device other than that which is applied to it by its drive means (19).
  22. A shutter arrangement according to any preceding claim, in which the drive means (19) of the device comprise an electromagnet.
  23. A shutter arrangement according to claim 22 in which the shutter (5) is in the closed position when the electromagnet is at rest.
  24. A shutter arrangement according to any preceding claim, in which an outlet shutter (25), controlled by the processor (21), allows a rejected document (20) to leave the selector.
  25. A shutter arrangement according to any preceding

claim, further comprising means for generating optical or acoustic signals to inform the user regarding obstruction of the inlet channel (26).

26. A shutter arrangement comprising a shutter member (5) including a passage (11) through which a document can pass, said passage being alignable with a document transport passage (26) of a document handling apparatus by pivoting the shutter assembly about a pivot axis (18), said shutter being located within a surround (70), characterised in that the surround (70) and the shutter (5) carry mutually interengaging features (17,60) to prevent a flat document from passing between the shutter and the surround.
27. A shutter arrangement according to claim 26 in which the shutter comprises a rotationally symmetrical (e.g. cylindrical) shutter (5).
28. A shutter arrangement according to claim 26 or 27 in which said features comprise castellation upon said shutter and/or said surround.

#### Patentansprüche

1. Verschlussanordnung für eine Dokumentenhandhabungsvorrichtung mit einem Kanal (26) und einem Verschluss (5), der den Kanal (26, 11, 22) blockieren kann, um eine Drehachse (18) in die oder aus der Ebene des Dokuments (20) drehbar ist und weitere Komponenten (8) aufweist, die sich mit ihm zusammen bewegen (beispielsweise zur Betätigung des Verschlusses), so daß ein Bewegungsmechanismus gebildet wird,  
dadurch gekennzeichnet, daß die Masse des Bewegungsmechanismus (5, 8) so verteilt ist, daß der Mechanismus bei Vibrationen der Dokumentenhandhabungsvorrichtung, mit der die Drehachse (18) verbunden ist, kein Drehmoment um die Drehachse (18) zeigt.
2. Verschlussanordnung nach Anspruch 1, deren Schwerpunkt auf der Drehachse (18) liegt.
3. Verschlussanordnung nach Anspruch 1, mit einem länglichen Betätigungselement (8), das sich von der Drehachse (18) weg erstreckt, wobei der Verschluss (5) mit dem Element (8) so verbunden ist, daß eine Betätigung des Elements (8) den Verschluss (5) dreht.
4. Verschlussanordnung nach Anspruch 1 oder 3, mit einer zweiten Drehachse (33) und einer Betätigungseinrichtung (8b, 9) zur Betätigung des Verschlusses (5), die sich um die zweite Drehachse (33) dreht, sowie mit einer um die zweite Achse her-

um wirkenden Gegengewichtsanordnung (35), die die Masse des Mechanismus so ausgleicht, daß er kein Drehmoment erzeugt.

5. Verschlussanordnung nach einem der vorhergehenden Ansprüche, wobei der Kanal (26) ein Einlaßkanal für die Dokumentenhandhabungsvorrichtung ist.
6. Verschlussanordnung nach einem der Ansprüche 1 bis 4, wobei der Kanal (26) ein zu einem Dokumentenauslaß der Dokumentenhandhabungsvorrichtung führender Auslaßkanal ist.
7. Verschlussanordnung nach einem der Ansprüche 1 bis 4, wobei sich der Kanal (26) in eine Vielzahl von Auslaßästen verzweigt und der Verschluss eine Ablenkeinrichtung (49) zur Auswahl eines der Auslaßäste aufweist.
8. Verschlussanordnung nach einem der vorhergehenden Ansprüche mit einer Verschlussantriebseinrichtung (19), die von einer Steuerschaltung (21) betätigt wird, die wiederum in Reaktion auf das Ansprechen eines oder mehrerer Systeme (3, 4) zur Erfassung des Vorhandenseins eines Papiers arbeitet, um den Verschluss durch Betätigung der Antriebseinrichtung (19) zu schließen.
9. Verschlussanordnung nach einem der vorhergehenden Ansprüche, wobei der Verschluss (5) den Kanal (26, 11, 22) über dessen ganze Breite blockiert.
10. Verschlussanordnung nach einem der vorhergehenden Ansprüche, wobei der Kanal (26) mit Einrichtungen ausgestattet ist, die in in dem Verschluss (5) vorgesehene, zusammenwirkende Einrichtungen (17, 60) eingreifen, um zu verhindern, daß das Dokument (20) um den Verschluss (5) herumläuft.
11. Verschlussanordnung nach einem der vorhergehenden Ansprüche, wobei der Verschluss (5) eine einem Zylinder einer Rotation um die Achse (18) ähnelnde Form aufweist und durch den Verschluss (5) hindurch mindestens ein Schlitz (11) vorgesehen ist, um in mindestens einer bestimmten Winkelposition des Apparats das Durchlaufen des Dokuments (20) zu erlauben.
12. Verschlussanordnung nach Anspruch 11, wobei der Schlitz bzw. die Schlitze (11) bezüglich der Achse (18) symmetrisch angeordnet sind.
13. Verschlussanordnung nach Anspruch 11 oder 12, wobei lediglich ein Schlitz (11) vorgesehen ist.
14. Verschlussanordnung nach einem der Ansprüche 11 bis 13, wobei der bzw. jeder Schlitz (11) einen ko-

nischen Einlaßabschnitt aufweist, der das Dokument (20) in den Schlitz (11) einzuführen gestattet.

15. Verschußanordnung nach Anspruch 11, wobei der Verschuß (5) zwei etwa senkrecht zueinander stehende Schlitze aufweist.
16. Verschußanordnung nach Anspruch 11, wobei der Verschuß zwei vorzugsweise etwa parallel zueinander ausgerichtete Schlitze aufweist und sich die Drehachse (18) außerhalb der Ebene des Einführens des Dokuments (20) in die Öffnung (16) befindet.
17. Verschußanordnung nach Anspruch 11, wobei der Verschuß (5) mehrteilig aus Materialien unterschiedlicher Dichte, die in unterschiedlichen Entfernungen von der Drehachse (18) angeordnet sind, aufgebaut ist.
18. Verschußanordnung nach einem der vorhergehenden Ansprüche, mit einer Einrichtung (10, 12, 14, 15) zur Erkennung der Position des Verschlusses (5).
19. Verschußanordnung nach Anspruch 18, wobei die Erkennungseinrichtung eine mit dem Verschuß (5) verbundene, sich mit diesem bewegende Kodierscheibe (10) umfaßt.
20. Verschußanordnung nach Anspruch 19, wobei mindestens vier mit gleichförmigem Abstand angeordnete Positionen des Verschlusses (5) von der Kodierscheibe (10) erkannt werden, zwei dieser Positionen dem vollständigen Öffnen des Verschlusses (5) und zwei andere seinem vollständigen Schließen entsprechen, und wobei der Prozessor (21) das Drehen des Verschlusses (5) in Reaktion auf den Betrieb der Erkennungseinrichtung (10, 12, 14, 15) anordnen kann.
21. Verschußanordnung nach einem der vorhergehenden Ansprüche, mit einer Einrichtung zur Erfassung einer anderen Belastung des Apparats als derjenigen, die an ihn von der Antriebseinrichtung (19) angelegt wird.
22. Verschußanordnung nach einem der vorhergehenden Ansprüche, wobei die Antriebseinrichtung (19) der Vorrichtung einen Elektromagneten aufweist.
23. Verschußanordnung nach Anspruch 22, wobei sich der Verschuß (5) bei Ruhen des Elektromagneten in geschlossener Position befindet.
24. Verschußanordnung nach einem der vorhergehenden Ansprüche, wobei ein von dem Prozessor (21) angesteuerter Auslaßverschuß (25) einem zurück-

gewiesenen Dokument (20) gestattet, die Wählvorrichtung zu verlassen.

25. Verschußanordnung nach einem der vorhergehenden Ansprüche, mit einer Einrichtung zur Erzeugung eines optischen oder akustischen Signals, um den Benutzer über die Blockierung des Einlaßkanals (26) zu informieren.
26. Verschußanordnung mit einem einen Durchlaß (11), durch den ein Dokument passieren kann, aufweisenden Schließelement (5), wobei der Durchlaß durch Drehen des Verschußmechanismus um eine Drehachse (18) auf einen Dokumententransportweg (26) einer Dokumentenhandhabungsvorrichtung ausgerichtet werden kann, und der Verschuß in einer Einfassung (70) angeordnet ist, dadurch gekennzeichnet, daß die Einfassung (70) und der Verschuß (5) wechselweise ineinander eingreifende Einrichtungen (17, 60) aufweisen, um zu verhindern, daß ein flaches Dokument zwischen Verschuß und Einfassung hindurchläuft.
27. Verschußanordnung nach Anspruch 26, wobei der Verschuß einen rotationssymmetrischen (beispielsweise zylindrischen) Verschuß (5) aufweist.
28. Verschußanordnung nach Anspruch 26 oder 27, wobei die genannten Einrichtungen eine Zinnenstruktur auf dem Verschuß und/oder der Einfassung aufweisen.

#### Revendications

1. Agencement d'obturateur pour un appareil de manipulation de documents, comprenant un canal (26), un clapet (5) susceptible d'obstruer le canal (26, 11, 12) et en rotation autour d'un axe de pivotement (18) situé dans ou en dehors du plan du document (20); le clapet comportant d'autres composants (8) susceptibles de se déplacer avec celui-ci (par exemple, pour actionner le clapet), de façon à définir un dispositif mobile, caractérisé en ce que la masse dudit dispositif mobile (5, 8) est répartie de façon que le dispositif ne présente aucun mouvement tournant autour dudit axe de pivotement (18) en cas de vibration de l'appareil de manipulation de documents auquel l'axe de pivotement (18) est connecté.
2. Agencement d'obturateur selon la revendication 1, dans lequel le centre de gravité du dispositif est situé sur l'axe de pivotement (18).
3. Agencement d'obturateur selon la revendication 1, qui comprend un organe d'actionnement allongé (8) s'étendant en s'éloignant dudit axe de pivotement

(18), ledit clapet (5) étant connecté audit organe (8) de façon que l'actionnement dudit organe (8) fasse pivoter ledit clapet (5).

4. Agencement d'obturateur selon la revendication 1, comprenant en outre un deuxième axe de pivotement (33), et des moyens d'actionnement (8b, 9) pour actionner ledit clapet (5), lesdits moyens d'actionnement (8b, 9) pivotant autour dudit deuxième axe de pivotement (33), comprenant en outre un agencement de contrepoids (35), agissant autour dudit deuxième axe pour équilibrer la masse du dispositif, de façon qu'il ne présente aucun moment rotatif.
5. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel ledit canal (26) est un canal d'entrée vers ledit appareil de manipulation de documents.
6. Agencement d'obturateur selon l'une quelconque des revendications 1 à 4, dans lequel ledit canal (26) est un canal de sortie conduisant à une sortie de documents de l'appareil de manipulation de documents.
7. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel le canal (26) se raccorde à une pluralité de branches de sortie, et le clapet comprend un dispositif de déviation (49) pour sélectionner l'une desdites branches de sortie.
8. Agencement d'obturateur selon l'une quelconque des revendications précédentes, comprenant des moyens d'entraînement de clapet (19) actionnés par un circuit de commande (21) agissant en réponse à l'action d'un ou de plusieurs systèmes (3, 4) pour détecter la présence de papier, afin de fermer le clapet (5) par actionnement des moyens d'entraînement (19).
9. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel le clapet (5) obstrue le canal (26, 11, 22) sur toute sa longueur.
10. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel le canal (26) est équipé d'éléments pouvant s'engager dans des éléments coopérants (17, 60), disposés autour du clapet (5), pour empêcher le document de passer autour du clapet (5).
11. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel le clapet (5) a une forme s'apparentant à celle d'un cylindre de révolution autour de l'axe (18), et au moins

une fente (11) est aménagée dans le clapet (5) pour permettre le passage du document (20) dans au moins une position angulaire définie du dispositif.

12. Agencement d'obturateur selon la revendication 11, dans lequel la fente ou les fentes (11) sont symétriques par rapport à l'axe (18).
13. Agencement d'obturateur selon la revendication 11 ou la revendication 12, dans lequel il n'y a qu'une seule fente (11).
14. Agencement d'obturateur selon l'une quelconque des revendications 11 à 13, dans lequel la ou chaque fente (11) comprend une partie d'entrée évasée permettant au document (20) d'être guidé dans la dite fente (11).
15. Agencement d'obturateur selon la revendication 11, dans lequel le clapet (5) comprend deux fentes approximativement normales entre elles.
16. Agencement d'obturateur selon la revendication 11, dans lequel le clapet (5) comprend deux fentes, de préférence généralement parallèles entre elles, l'axe de pivotement (18) étant situé en dehors du plan d'introduction du document (20) dans l'embouchure (16).
17. Agencement d'obturateur selon la revendication 11, dans lequel le clapet (5) est réalisé en plusieurs pièces constituées de matériaux de densités différentes, réparties à des distances différentes de l'axe de pivotement (18).
18. Agencement d'obturateur selon l'une quelconque des revendications précédentes, comprenant en outre des moyens (10, 12, 14, 15) pour repérer la position du clapet (5).
19. Agencement d'obturateur selon la revendication 18, dans lequel les moyens d'identification comprennent un disque encodeur (10) solidaire du clapet (5) pour se déplacer avec celui-ci.
20. Agencement d'obturateur selon la revendication 19, dans lequel les positions du clapet (5) repérées par le disque encodeur (10) sont au moins au nombre de quatre et régulièrement espacées, deux desdites positions correspondant à l'ouverture complète du clapet (5), et deux autres à sa fermeture complète, et dans lequel le processeur (21), en réponse à l'action des moyens de repérage (10, 12, 14, 15), peut ordonner la rotation du clapet (5).
21. Agencement d'obturateur selon l'une quelconque des revendications précédentes, comprenant des moyens pour détecter une sollicitation du dispositif

autre que celle qui lui est appliquée par ses moyens d'entraînement (19).

22. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel les moyens d'entraînement (19) du dispositif comprennent un électro-aimant. 5
23. Agencement d'obturateur selon la revendication 22, dans lequel le clapet (5) est en position fermée lorsque l'électro-aimant est au repos. 10
24. Agencement d'obturateur selon l'une quelconque des revendications précédentes, dans lequel un clapet de sortie (25), commandé par le processeur (21), permet la sortie du sélecteur d'un document (20) refusé. 15
25. Agencement d'obturateur selon l'une quelconque des revendications précédentes, comprenant en outre des moyens pour générer des signaux optiques ou sonores pour renseigner l'utilisateur sur l'obstruction du canal d'entrée (26). 20
26. Agencement d'obturateur comprenant un organe formant clapet (5), comportant un passage (11) qu'un document peut traverser, ledit passage pouvant être aligné avec un passage de transport de documents (26) d'un appareil de manipulation de documents, par rotation du dispositif formant clapet autour d'un axe de pivotement (18), ledit clapet étant situé à l'intérieur d'un encadrement (70), caractérisé en ce que l'encadrement (70) et le clapet (5) portent des éléments en engagement mutuel (17, 60), pour empêcher un document plat de passer entre le clapet et l'encadrement. 25  
30  
35
27. Agencement d'obturateur selon la revendication 26, dans lequel le clapet est constitué d'un clapet (5) symétrique en rotation (par exemple, cylindrique). 40
28. Agencement d'obturateur selon la revendication 26 ou 27, dans lequel lesdits éléments comprennent un créneau sur ledit clapet et/ou ledit encadrement. 45

50

55

FIG. 1






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11







FIG. 13









FIG. 16




FIG. 18




FIG. 19




FIG. 20

